

How to mount the roof box

A short instruction

Included in delivery

- 4 pieces of U-Bolts each with two thumbscrews and protective caps, one plate and 4 pieces of T-adapters
- Different possibilities to mount: if you use T-adapters then take the thumbscrews of the U-Bolts
- Tension belts, for example to fix the skis and equipment in the box in general



- 2 keys (1 key extra)

Step 1: Check the roof rack

- Our roof boxes can be mounted on every typical roof rack
- In case you have a roof rack called „Votex“ (for example of companies like VW/Audi) with an inserted C-profile you can mount the roof box instead of U-Bolts with the T-adapter kit
- -> Please assemble the existing roof rack as instructed by the producer on the roof of your car
 - > Choose between mounting the box with U-Bolts or T-adapters
- > An explanation for both is following:

Example of a correct installation of a roof rack



Step 2)

Either: mounting the
box with T-adapters

Open the cover at
the side

-> Then put in the
T-adapter



Lift the box and
place the T-adapter
in each case under
the slot



Drop the box and close the cover of the roof rack



-> Now you can see the T-adapter in the box



Put the plate on the
T-adapter



Use the thumbscrew
to screw it



Or: Put the box on roof rack (mounting with U-Bolts)

- Look at the hole pattern
- Install the roof box on the roof rack with a distance of the U-Bolts as large as possible
- Lead the U-Bolts in each case around the traverse in the roof box
- Put the rectangular plates on the endpiece of the U-Bolts; Use the thumbscrews to screw it
- Then put the protective caps on the endpieces of the U-Bolts

Lead the U-Bolts around the traverse
in the box; put on the plate and screw
it



Step 3: How to adjust the box

- In longitudinal direction: neither ahead, nor behind the box should jut out the shape of the car
 - In transverse direction: install the box as much as possible in center
- > balanced load distribution and aerodynamical upstream-flow



How you use the box

- Usually you can open the boot lid without any problems
- By pushing the lock you can open the box
- The band is useful to close the box



Hints for care

- Clean the locks best with gun-oil
- Do not use an open flame for defrosting
- Keep the plungers of the gas pressure dampers clean and dry
- Please do not use care products

Hints for safety

- The roof load stated by the car-producer should not be exceeded
- Please make sure that the box is closed before you drive
- The driving characteristics of the car is influenced by the box
- -> adjust your driving style and speed
- Please check the bolted connection as often as possible and fix it if necessary

Caution!

- When closing the box, please make sure that the belt is inside the box and that it's not engaged in the lock!

Have a good trip!

Your MOBILA-Team