

# How to mount the surfbox

A short instruction

# Included in delivery

- 4 pieces of U-Bolts each with two thumbscrews, protective caps and one plate
- Different possibilities to mount: if you use T-adapters then take the thumbscrews of the U-Bolts
- Tension belts, for example to fix the skis and equipment in the box in general



-> 4 X

- 2 keys ( 1 key extra )

# Step 1: Check the roof rack

- Our roof boxes can be mounted on every typical roof rack
- In case you have a roof rack called „Votex“ ( for example of companies like VW/Audi) with an inserted C-profile you can mount the roof box instead of U-Bolts with the extra available T-adapter kit (**with costs**)
- -> Please assemble the existing roof rack as instructed by the producer on the roof of your car
- Choose between mounting the box with U-Bolts or T-adapters ( In case you have ordered the T-adapters extra )
- Be aware that the maximum load with T-adapters is **95 kg**
- An explanation for both mounting possibilities is following

# Example of a correct installation of a roof rack



## Step 2: Put the box on roof rack (mounting with U-Bolts)

- Look at the hole pattern
- Install the roof box on the roof rack with a distance of the U-Bolts as large as possible
- Lead the U-Bolts in each case around the traverse in the roof box
- Put the rectangular plates on the endpiece of the U-Bolts; Use the thumbscrews to screw it
- Then put the protective caps on the endpieces of the U-Bolts

Lead the U-Bolts around the traverse  
in the box; put on the plate and screw  
it



Alternatively:  
mounting the box with  
T-adapters

Open the cover at  
the side

-> Then put in the  
T-adapter



Lift the box and  
place the T-adapter  
in each case under  
the slot



Drop the box and  
close the cover of  
the roof rack

-> Now you can see  
the T-adapter in the  
box



Put the plate on the  
T-adapter



Use the thumbscrew  
to screw it



# Step 3: How to adjust the box

- In longitudinal direction: neither ahead, nor behind the box should jut out the shape of the car
  - In transverse direction: install the box as much as possible in center
- > balanced load distribution and aerodynamical upstream-flow



# How you use the box

- Usually you can open the boot lid without any problems
- By pushing the lock you can open the box
- The band is useful to close the box



# Hints for care

- Clean the locks best with gun-oil
- Do not use an open flame for defrosting
- Keep the plungers of the gas pressure dampers clean and dry
- Please do not use care products

# Hints for safety

- The roof load stated by the car-producer should not be exceeded
- Please make sure that the box is closed before you drive
- The driving characteristics of the car is influenced by the box
- -> adjust your driving style and speed
- Please check the bolted connection as often as possible and fix it if necessary

# Caution!

- When closing the box, please make sure that the belt is inside the box and that it's not engaged in the lock!

# Have a good trip!

Your MOBILA-Team